

# Safety Data Sheet

CERAMIC POLYMER  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartidge Part A

Print date: 30.05.2016

Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

CN-OC Cartidge Part A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Coatings and paints, fillers, putties, thinners

##### Uses advised against

No information available.

#### 1.3. Details of the supplier of the safety data sheet

Company name:	Ceramic Polymer GmbH	
Street:	Daimlerring 9	
Place:	D-D-32289 Rödighausen	
Telephone:	+49(0) 52 23 / 9 62 76-0	Telefax: +49(0) 52 23 / 9 62 76-17
e-mail:	info@ceramic-polymer.de	
Internet:	www.ceramic-polymer.de	
Responsible Department:	info@ceramic-polymer.de	

#### 1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1C  
Serious eye damage/eye irritation: Eye Dam. 1  
Respiratory or skin sensitisation: Skin Sens. 1  
Reproductive toxicity: Repr. 1B  
Hazardous to the aquatic environment: Aquatic Chronic 2  
Hazard Statements:  
Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
May damage fertility.  
Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol  
Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane  
Phenol, polymer with formaldehyde, glycidether

Signal word: Danger

Pictograms:



##### Hazard statements

H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.

# Safety Data Sheet

CERAMIC POLYMER  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 2 of 12

H360F May damage fertility.  
H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P309+P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P273 Avoid release to the environment.  
P270 Do not eat, drink or smoke when using this product.  
P403+P235 Store in a well-ventilated place. Keep cool.

### Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			25-30 %
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			
30499-70-8	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane			25-30 %
			01-2120078341-60	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 2; H360F H314 H318 H317 H411			
28064-14-4	Phenol, polymer with formaldehyde, glycidether			15-20 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
78-93-3	butanone			1-3 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

# Safety Data Sheet

**CERAMIC POLYMER**  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 3 of 12

### **After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately.  
Do not wash with: Solvents/Thinner

### **After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

### **After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.  
Do NOT induce vomiting.

### **4.2. Most important symptoms and effects, both acute and delayed**

Immediate medical treatment required because corrosive injuries that are not treated are hard to cure. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

### **4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.  
After contact with skin, wash immediately with plenty of Lutrol.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). alcohol resistant foam. Water spray jet

#### **Unsuitable extinguishing media**

High power water jet

### **5.2. Special hazards arising from the substance or mixture**

Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>)

### **5.3. Advice for firefighters**

Special protective equipment for firefighters: Protective clothing. In case of fire: Wear self-contained breathing apparatus.  
Co-ordinate fire-fighting measures to the fire surroundings.

### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8.  
Provide adequate ventilation.  
Personal protection equipment: see section 8  
Remove persons to safety.

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### **6.4. Reference to other sections**

See protective measures under point 7 and 8.  
Disposal: see section 13

## **SECTION 7: Handling and storage**

# Safety Data Sheet

CERAMIC POLYMER  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 4 of 12

### 7.1. Precautions for safe handling

#### Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8). Keep container tightly closed.

#### Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

#### Advice on storage compatibility

Keep away from:

Food and feedingstuffs

Oxidising agent

#### Further information on storage conditions

Keep away from:

Frost

Heat

Humidity

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 5 of 12

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, acute		dermal	local	0,0083 mg/cm <sup>2</sup>
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	62,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	6,25 mg/kg bw/day
30499-70-8	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane			
Worker DNEL, long-term		inhalation	systemic	1,17 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,67 mg/kg bw/day
78-93-3	butanone			
Consumer DNEL, long-term		oral	systemic	31 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	412 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	106 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	600 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	1161 mg/kg bw/day

# Safety Data Sheet

CERAMIC POLYMER  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 6 of 12

### PNEC values

CAS No	Substance	Value
	Environmental compartment	
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	
	Freshwater	0,003 mg/l
	Freshwater sediment	0,294 mg/kg
	Marine sediment	0,029 mg/kg
	Soil	0,237 mg/kg
30499-70-8	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane	
	Freshwater	0,004 mg/l
	Freshwater (intermittent releases)	0,037 mg/l
	Freshwater sediment	0,02 mg/kg
	Marine sediment	0,002 mg/kg
	Soil	0,002 mg/kg
78-93-3	butanone	
	Freshwater	55,8 mg/l
	Marine water	55,8 mg/l
	Freshwater sediment	284,74 mg/kg
	Marine sediment	284,7 mg/kg
	Secondary poisoning	1000 mg/kg
	Soil	22,5 mg/kg

### 8.2. Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

#### Eye/face protection

Suitable eye protection:

Eye glasses with side protection  
goggles

#### Hand protection

Suitable gloves type:

NBR (Nitrile rubber) DIN EN 374,  
Butyl caoutchouc (butyl rubber) DIN EN 374  
Wear cotton undermitten if possible.

#### Skin protection

Protective clothing

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device (EN 14387) A-P3

Self-contained respirator (breathing apparatus) (DIN EN 133)

# Safety Data Sheet

CERAMIC POLYMER  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 7 of 12

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid  
Colour:  
Odour: characteristic

#### Test method

pH-Value: not determined

#### Changes in the physical state

Melting point: not determined  
Initial boiling point and boiling range: not determined  
Sublimation point: not determined  
Softening point: not determined  
Pour point: not determined  
Flash point: > 100 °C

#### Flammability

Solid: not determined  
Gas: not determined

#### Explosive properties

No information available.

Lower explosion limits: not determined  
Upper explosion limits: not determined  
Ignition temperature: not determined

#### Auto-ignition temperature

Solid: not determined  
Gas: not determined

Decomposition temperature: not determined

#### Oxidizing properties

No information available.

Vapour pressure: not determined

Density (at 20 °C): ~1,3 g/cm<sup>3</sup>

Water solubility: not determined

#### Solubility in other solvents

No information available.

Partition coefficient: not determined

Viscosity / dynamic: not determined

Vapour density: not determined

Evaporation rate: not determined

#### 9.2. Other information

No information available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

# Safety Data Sheet

CERAMIC POLYMER  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 8 of 12

### 10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

Reacts with: Acid, Oxidising agent

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

### 10.5. Incompatible materials

Acid, Oxidising agent

### 10.6. Hazardous decomposition products

Does not decompose when used for intended uses. No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Exposure route	Dose	Species	Source
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	oral	LD50 >5000 mg/kg	rat (male/female)	ECHA
		dermal	LD50 >2000 mg/kg	rat (male/female)	ECHA
30499-70-8	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane	oral	LD50 3398 mg/kg	Rat	OECD Guideline 401
		dermal	LD50 > 3170 mg/kg	Rat	OECD Guideline 402
78-93-3	butanone	oral	LD50 3300 mg/kg	Rat	IUCLID
		dermal	LD50 6400 - 8000 mg/kg	Rabbit	Supplier
		inhalative (4 h) aerosol	LC50 34,5 mg/l	Rat	

#### Irritation and corrosivity

Causes severe skin burns and eye damage.

#### Sensitising effects

May cause an allergic skin reaction. (Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane), (Phenol, polymer with formaldehyde, glycidether)

#### Carcinogenic/mutagenic/toxic effects for reproduction

May damage fertility. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

# Safety Data Sheet

CERAMIC POLYMER  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 9 of 12

### Aspiration hazard

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d]	Species	Source
78-93-3	butanone				
	Acute fish toxicity	LC50 2993 mg/l	96 h	Pimephales promelas	OECD Guideline 203
	Acute algae toxicity	ErC50 2029 mg/l	96 h	Selenastrum capricornutum	OECD Guideline 201
	Acute crustacea toxicity	EC50 308 mg/l	48 h	Daphnia magna	OECD Guideline 202
	Acute bacteria toxicity	(1150 mg/l)		Pseudomonas putida	Supplier

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Dispose of waste according to applicable legislation.

#### Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1760
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, N.O.S. (epoxy resin)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Classification code:	C9
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1760
-------------------------	---------

# Safety Data Sheet

CERAMIC POLYMER  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 10 of 12

<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, N.O.S. (epoxy resin)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Classification code:	C9
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1760
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, N.O.S. (epoxy resin)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Marine pollutant:	p
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B

### Air transport (ICAO)

<b>14.1. UN number:</b>	UN 1760
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, N.O.S. (epoxy resin)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	yes
Danger releasing substance:	epoxy resin

### 14.6. Special precautions for user

No information available.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulatory information

# Safety Data Sheet

CERAMIC POLYMER  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 11 of 12

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.
Water contaminating class (D):	2 - water contaminating

### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:  
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol  
Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane  
butanone

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 1.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international conernat le transport des marchandises dangereuses par chemin de fer  
(Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
EC50: Effectice concentration, 50 percent  
DNEL: Derived No Effect Level  
PNEC: Predicted No Effect Concentration  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H360F	May damage fertility.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of

# Safety Data Sheet

**CERAMIC POLYMER**  
ULTRA • PERFORM • COAT

according to Regulation (EC) No 1907/2006

## CN-OC Cartridge Part A

Print date: 30.05.2016

Page 12 of 12

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*