

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 1 of 17

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Proguard CN-OC V15 K3 Part B

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### **Use of the substance/mixture**

Coatings and paints, fillers, putties, thinners

###### **Uses advised against**

No data available

##### 1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	DE-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

##### 1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### **Regulation (EC) No. 1272/2008**

Hazard categories:

Acute toxicity: Acute Tox. 4

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful if swallowed.

Harmful if inhaled.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

##### 2.2. Label elements

###### **Regulation (EC) No. 1272/2008**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 2 of 17

#### Hazard components for labelling

benzyl alcohol  
3-aminomethyl-3,5,5-trimethylcyclohexylamine  
m-phenylenebis(methylamine)  
3-aminopropyltriethoxysilane

**Signal word:** Danger

**Pictograms:**



#### Hazard statements

H302+H332 Harmful if swallowed or if inhaled.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 3 of 17

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
100-51-6	benzyl alcohol			25-33 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			16-23 %
	220-666-8	612-067-00-9	01-2119514687-32	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H317 H412			
1477-55-0	m-phenylenebis(methylamine)			12-22 %
	216-032-5		01-2119480150-50	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1, Skin Sens. 1, Aquatic Chronic 3; H332 H302 H314 H317 H412 EUH071			
135470-04-1	1,3-Benzenedimethanamine, reaction products with epichlorohydrin			5-10 %
	Aquatic Chronic 2; H411			
919-30-2	3-aminopropyltriethoxysilane			0,5 - 2 %
	213-048-4	612-108-00-0	01-2119480479-24	
	Acute Tox. 4, Skin Corr. 1B; H302 H314			

Full text of H and EUH statements: see section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

###### After inhalation

In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

###### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately.  
Do not wash with: Solvents/Thinner

###### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

###### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.  
Do NOT induce vomiting.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 4 of 17

#### **4.2. Most important symptoms and effects, both acute and delayed**

Immediate medical treatment required because corrosive injuries that are not treated are hard to cure. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.  
After contact with skin, wash immediately with plenty of Lutrol.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). alcohol resistant foam. Water spray jet

##### **Unsuitable extinguishing media**

Full water jet

#### **5.2. Special hazards arising from the substance or mixture**

Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>)

#### **5.3. Advice for firefighters**

Special protective equipment for firefighters Protective clothing. In case of fire: Wear self-contained breathing apparatus.  
Co-ordinate fire-fighting measures to the fire surroundings.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8.  
Provide adequate ventilation.  
Personal protection equipment: see section 8  
Remove persons to safety.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### **6.4. Reference to other sections**

See protective measures under point 7 and 8. Disposal: see section 13

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

See section 8. Wear personal protection equipment (refer to section 8). Keep container tightly closed.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 5 of 17

#### **Advice on protection against fire and explosion**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

##### **Hints on joint storage**

Keep away from:

Food and feedingstuffs

Oxidising agent

##### **Further information on storage conditions**

Keep away from:

Frost

Heat

Humidity

#### **7.3. Specific end use(s)**

No information available.

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 6 of 17

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
100-51-6	benzyl alcohol			
Worker DNEL, long-term		inhalation	systemic	22 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	110 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	5,4 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	27 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	4 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	20 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	20 mg/kg bw/day
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			
Worker DNEL, long-term		inhalation	local	0,073 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	0,073 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	0,526 mg/kg bw/day
1477-55-0	m-phenylenebis(methylamine)			
Worker DNEL, long-term		dermal	systemic	0,33 mg/kg bw/day
Worker DNEL, long-term		inhalation	local	0,2 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	1,2 mg/m <sup>3</sup>
919-30-2	3-aminopropyltriethoxysilane			
Worker DNEL, long-term		inhalation	systemic	59 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	59 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	8,3 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	8,3 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	17,4 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	17,4 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	5 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	5 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 7 of 17

#### PNEC values

CAS No	Substance	Value
100-51-6	benzyl alcohol	
Freshwater		1 mg/l
Freshwater (intermittent releases)		2,3 mg/l
Marine water		0,1 mg/l
Freshwater sediment		5,27 mg/kg
Marine sediment		0,527 mg/kg
Micro-organisms in sewage treatment plants (STP)		39 mg/l
Soil		0,456 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Freshwater		0,06 mg/l
Freshwater (intermittent releases)		0,23 mg/l
Marine water		0,006 mg/l
Freshwater sediment		5,784 mg/kg
Marine sediment		0,578 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,18 mg/l
Soil		1,121 mg/kg
1477-55-0	m-phenylenebis(methylamine)	
Freshwater		0,094 mg/l
Freshwater (intermittent releases)		0,152 mg/l
Marine water		0,009 mg/l
Freshwater sediment		12,4 mg/kg
Marine sediment		1,24 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		2,44 mg/kg
919-30-2	3-aminopropyltriethoxysilane	
Freshwater		0,33 mg/l
Freshwater (intermittent releases)		3,3 mg/l
Marine water		0,033 mg/l
Freshwater sediment		1,2 mg/kg
Marine sediment		0,12 mg/kg
Micro-organisms in sewage treatment plants (STP)		13 mg/l
Soil		0,05 mg/kg

#### 8.2. Exposure controls

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 8 of 17

#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

#### Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

#### Eye/face protection

Suitable eye protection:  
Eye glasses with side protection  
goggles

#### Hand protection

Tested protective gloves must be worn: EN ISO 374  
NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)  
Wearing time with permanent contact: Thickness of the glove material:  $\geq 0,4$  mm, Breakthrough time (maximum wearing time):  $>480$  min  
Wearing time with occasional contact (splashes):: Thickness of the glove material:  $\geq 0,1$  mm, Breakthrough time (maximum wearing time)  $> 30$  min  
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
Breakthrough times and swelling properties of the material must be taken into consideration.

#### Skin protection

Protective clothing

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.  
Combination filtering device (EN 14387) A-P3  
Self-contained respirator (breathing apparatus) (DIN EN 133)

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	light yellow
Odour:	like amines
pH-Value:	~11

#### Changes in the physical state

Melting point:	No data available
Initial boiling point and boiling range:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
Flash point:	$>65$ °C

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 9 of 17

#### Flammability

Solid: No data available  
Gas: No data available

#### Explosive properties

No information available.

Lower explosion limits: No data available  
Upper explosion limits: No data available  
Ignition temperature: No data available

#### Auto-ignition temperature

Solid: No data available  
Gas: No data available

Decomposition temperature: No data available

#### Oxidizing properties

No information available.

Vapour pressure:  
(at 25 °C) No data available

Density (at 23 °C): ca. 1,06 g/cm<sup>3</sup>

Water solubility: partially soluble

#### Solubility in other solvents

No information available.

Partition coefficient: No data available

Viscosity / dynamic: ca. 500 mPa·s

Vapour density: No data available

Evaporation rate: No data available

#### 9.2. Other information

No information available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Acid, Oxidising agent

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

#### 10.5. Incompatible materials

Acid, Oxidising agent

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 10 of 17

#### 10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

Harmful if swallowed.

Harmful if inhaled.

##### ATEmix calculated

ATE (oral) 1831,5 mg/kg; ATE (inhalation aerosol) 3,297 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
100-51-6	benzyl alcohol				
	oral	LD50 mg/kg 1580	Mouse	Cosmet. Toxicol. 11, 1011-1013 (1973) (1)	OECD Guideline 401
	dermal	LD50 mg/kg > 2000	Rabbit	Raw Material Data Handbook, Vol.1:( Orga	EPA OTS 798.1100
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) aerosol	LC50 mg/l >4,178	Rat	ECHA	OECD 403
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	LD50 mg/kg 1030	Rat	Study report (1965)	OECD Guideline 401
	dermal	LD50 mg/kg > 2000	Rat	Study report (2010)	OECD Guideline 402
1477-55-0	m-phenylenebis(methylamine)				
	oral	LD50 mg/kg 930	Rat	Study report (1973)	OECD Guideline 401
	dermal	LD50 mg/kg > 3100	Rat	Study report (1975)	TK 11813 was applied to a shaved area of
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) aerosol	LC50 mg/l 1,34	Rat		
919-30-2	3-aminopropyltriethoxysilane				
	oral	LD50 mg/kg 530	Mouse	Study report (1972)	No details of a guideline and only limit

##### Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 11 of 17

#### **Sensitising effects**

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; m-phenylenebis(methylamine))

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

Based on available data, the classification criteria are not met.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1. Toxicity

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 12 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
100-51-6	benzyl alcohol					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oryzias latipes	Review article or handbook (2009)	OECD Guideline 203
	Acute algae toxicity	ErC50 770 mg/l	72 h	Pseudokirchneriella subcapitata	Review article or handbook (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 230 mg/l	48 h	Daphnia magna	Review article or handbook (2009)	OECD Guideline 202
	Fish toxicity	NOEC 48,897 mg/l	30 d	Fish species	<a href="http://epa.gov/oppt/exposure/pubs/episui">http://epa.gov/oppt/exposure/pubs/episui</a>	other: QSAR
	Algae toxicity	NOEC 51 mg/l	3 d			
	Crustacea toxicity	NOEC 51 mg/l	21 d	Daphnia magna	Review article or handbook (2009)	OECD Guideline 211
	Acute bacteria toxicity	(1385 mg/l)	3 h	activated sludge, domestic	Study report (1989)	OECD Guideline 209
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine					
	Acute fish toxicity	LC50 110 mg/l	96 h	Leuciscus idus	Study report (1993)	EU Method C.1
	Acute algae toxicity	ErC50 37 mg/l	72 h	Desmodesmus subspicatus	Study report (1993)	EU Method C.3
	Acute crustacea toxicity	EC50 23 mg/l	48 h	Daphnia magna	Study report (2002)	OECD Guideline 202
	Crustacea toxicity	NOEC 3 mg/l	21 d	Daphnia magna	Study report (1993)	other: OECD 202, part 2
1477-55-0	m-phenylenebis(methylamine)					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 15,2 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	(> 1000 mg/l)	0,5 h	Activated sludge from laboratory wastewater plant	Study report (2004)	OECD Guideline 209
919-30-2	3-aminopropyltriethoxysilane					
	Acute fish toxicity	LC50 > 934 mg/l	96 h	Danio rerio	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Desmodesmus subspicatus	Study report (1994)	EU Method C.3
	Acute crustacea toxicity	EC50 331 mg/l	48 h	Daphnia magna	Study report (1993)	OECD Guideline 202

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 13 of 17

#### 12.2. Persistence and degradability

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
100-51-6	benzyl alcohol	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	95 - 97%	21	
	Readily biodegradable (according to OECD criteria).				
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	8 %	28	
	Not readily biodegradable (according to OECD criteria)				
1477-55-0	m-phenylenebis(methylamine)	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	49 %	28	
	Not readily biodegradable (according to OECD criteria)				
919-30-2	3-aminopropyltriethoxysilane		68	28	

#### 12.3. Bioaccumulative potential

No information available.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-51-6	benzyl alcohol	1
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0,99
1477-55-0	m-phenylenebis(methylamine)	ca. 0,18
919-30-2	3-aminopropyltriethoxysilane	1,7

#### BCF

CAS No	Chemical name	BCF	Species	Source
100-51-6	benzyl alcohol	1,371	QSAR model	<a href="http://epa.gov/oppt/">http://epa.gov/oppt/</a>
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	3,16	QSAR estimate	Other company data (
1477-55-0	m-phenylenebis(methylamine)	3,16	no data	Validated suite of c
919-30-2	3-aminopropyltriethoxysilane	3,4	Cyprinus carpio	Other company data (

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 14 of 17

#### Disposal recommendations

Dispose of waste according to applicable legislation.

#### Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 2735
<b>14.2. UN proper shipping name:</b>	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine, m-phenylenebis(methylamine))
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

#### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 2735
<b>14.2. UN proper shipping name:</b>	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine, m-phenylenebis(methylamine))
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

#### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 2735
<b>14.2. UN proper shipping name:</b>	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine, m-phenylenebis(methylamine))
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 15 of 17

Segregation group: alkalis

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 2735

**14.2. UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine, m-phenylenebis(methylamine))

**14.3. Transport hazard class(es):** 8

**14.4. Packing group:** II

Hazard label: 8

Special Provisions: A3 A803

Limited quantity Passenger: 0.5 L

Passenger LQ: Y840

Excepted quantity: E2

IATA-packing instructions - Passenger: 851

IATA-max. quantity - Passenger: 1 L

IATA-packing instructions - Cargo: 855

IATA-max. quantity - Cargo: 30 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.6. Special precautions for user

No information available.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: 3-aminopropyltriethoxysilane

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

##### National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

#### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(methylamine)

3-aminopropyltriethoxysilane

### SECTION 16: Other information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 16 of 17

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,11,15.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road )  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer  
(Regulations Concerning the International Transport of Dangerous Goods by Rail )  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
CLP: Classification, labelling and Packaging  
REACH: Registration, Evaluation and Authorization of Chemicals  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
UN: United Nations  
CAS: Chemical Abstracts Service  
DNEL: Derived No Effect Level  
DMEL: Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
ATE: Acute toxicity estimate  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%  
LL50: Lethal loading, 50%  
EL50: Effect loading, 50%  
EC50: Effective Concentration 50%  
ErC50: Effective Concentration 50%, growth rate  
NOEC: No Observed Effect Concentration  
BCF: Bio-concentration factor  
PBT: persistent, bioaccumulative, toxic  
vPvB: very persistent, very bioaccumulative  
MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
IBC: Intermediate Bulk Container  
SVHC: Substance of Very High Concern

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Corr. 1; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Proguard CN-OC V15 K3 Part B

Revision date: 06.12.2019

Page 17 of 17

H302+H332	Harmful if swallowed or if inhaled.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*