

Revision date: 13.04.2016

according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

CP-Synthofloor 8463 Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coatings and paints, fillers, putties, thinners

1.3. Details of the supplier of the safety data sheet

Company name: Ceramic Polymer GmbH

Street: Daimlerring 9

Place: DE-32289 Rödinghausen
Telephone: +49(0) 52 23 / 9 62 76-0 Telefax: +49(0) 52 23 / 9 62 76-17

e-mail: info@ceramic-polymer.de Internet: www.ceramic-polymer.de Responsible Department: info@ceramic-polymer.de

1.4. Emergency telephone +49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Signal word: Warning

Pictograms:





Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.



Revision date: 13.04.2016

according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A				
Print date: 28.04.2016		Page 2 of 11		
P309+P311	IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.			
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.			
P337+P313	If eye irritation persists: Get medical advice/attention.			
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
P362+P364	Take off contaminated clothing and wash it before reuse.			
P273	Avoid release to the environment.			
P270	Do not eat, drink or smoke when using this product.			
P403+P233	Store in a well-ventilated place. Keep container tightly closed.			

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	Classification according to Regula	•		
25068-38-6	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane			25-50 %
	500-033-5	603-074-00-8	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			5-25 %
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatio			
68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs			<10 %
	271-846-8	603-103-00-4	01-2119485289-22	
	Skin Irrit. 2, Skin Sens. 1; H315 H317			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately. Do not wash with: Solvents/Thinner

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After indestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.



Revision date: 13.04.2016

according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 3 of 11

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

After contact with skin, wash immediately with plenty of Lutrol.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO2). alcohol resistant foam. Water spray jet

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx)

5.3. Advice for firefighters

Special protective equipment for firefighters: Protective clothing. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

Provide adequate ventilation.

Personal protection equipment: see section 8

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8). Keep container tightly closed.

Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.



Revision date: 13.04.2016

according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 4 of 11

Advice on storage compatibility

Keep away from: Food and feedingstuffs Oxidising agent

Further information on storage conditions

Keep away from:

Frost

Heat

Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



Revision date: 13.04.2016

according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 5 of 11

DNEL/DMEL values

CAS No Substance			
ONEL type	Exposure route	Effect	Value
25068-38-6 4,4'-Isopropylidenediphenol, oligomeric re	eaction products with 1-chloro-2,3-ep	oxypropane	
Worker DNEL, long-term	inhalation	systemic	12,25 mg/m³
Worker DNEL, acute	inhalation	systemic	12,25 mg/m³
Norker DNEL, long-term	dermal	systemic	8,33 mg/kg bw/day
Norker DNEL, acute	dermal	systemic	8,33 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic 3,571 mg/k bw/day	
Consumer DNEL, acute	dermal	systemic	3,571 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,75 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	0,75 mg/kg bw/day
,			
9003-36-5 Formaldehyde, oligomeric reaction produ	ucts with 1-chloro-2,3-epoxypropane	and phenol	
Worker DNEL, long-term	inhalation	systemic	29,39 mg/m³
Norker DNEL, long-term	dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, acute	dermal	local	0,0083 mg/cm ²
Consumer DNEL, long-term	inhalation	systemic	8,7 mg/m³
Consumer DNEL, long-term	dermal	systemic	62,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	6,25 mg/kg bw/day
, Oxirane, mono[(C12-14-alkyloxy)methyl]	derivs		
Worker DNEL, long-term	inhalation	systemic	3,6 mg/m³
Worker DNEL, long-term	dermal	systemic	1 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,87 mg/m³
Consumer DNEL, long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,5 mg/kg bw/day
Series		0,0.00	o,o mg/ng sw/day



according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 6 of 11

PNEC values

	•		
CAS No	Substance		
Environmental compartment		Value	
25068-38-6	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		
Freshwater		0,006 mg/l	
Marine water		0,001 mg/l	
Freshwater sediment		0,996 mg/kg	
Marine sediment		0,1 mg/kg	
Secondary poisoning		11 mg/kg	
Soil		0,196 mg/kg	
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol		
Freshwater 0,003 m		0,003 mg/l	
Freshwater sediment		0,294 mg/kg	
Marine sediment		0,029 mg/kg	
Soil		0,237 mg/kg	
68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
Freshwater		0,007 mg/l	
Marine water		0,001 mg/l	
Freshwater sediment		307,16 mg/kg	
Marine sediment		30,72 mg/kg	
Soil		61,42 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

Eye/face protection

Suitable eye protection:

Eye glasses with side protection

goggles

Hand protection

Suitable gloves type:

NBR (Nitrile rubber) DIN EN 374,

Butyl caoutchouc (butyl rubber) DIN EN 374

Wear cotton undermitten if possible.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn

Combination filtering device (EN 14387) A-P3

Self-contained respirator (breathing apparatus) (DIN EN 133)



according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 7 of 11

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

liquid

Colour:

Odour:

pH-Value:

characteristic

Test method

not determined

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Sublimation point:

Softening point:

Pour point:

Flash point:

not determined

not determined

not determined

not determined

not determined

not determined

> 100 °C

Flammability

Solid: not determined
Gas: not determined

Explosive properties

No information available.

Lower explosion limits:

Upper explosion limits:

Ignition temperature:

not determined

not determined

Auto-ignition temperature

Solid: not determined
Gas: not determined

Decomposition temperature: not determined

Oxidizing properties

No information available.

Vapour pressure: not determined

Density (at 23 °C): 1,8 g/cm³

Water solubility: not determined

Solubility in other solvents

No information available.

Partition coefficient: not determined
Viscosity / dynamic: 6200 mPa·s

(at 23 °C)

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.



Revision date: 13.04.2016

according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 8 of 11

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reacts with: Acid, Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Acid, Oxidising agent

10.6. Hazardous decomposition products

Does not decompose when used for intended uses. Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose		Species	Source
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol				
	oral	LD50	>5000 mg/kg	rat (male/female)	ECHA
	dermal	LD50	>2000 mg/kg	rat (male/female)	ECHA

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane), (Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.



Revision date: 13.04.2016

according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 9 of 11

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9Classification code:M6

Special Provisions: 274 335 601

Limited quantity: 5 L
Transport category: 3
Hazard No: 90
Tunnel restriction code: E

Other applicable information (land transport)

E1

Inland waterways transport (ADN)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9Classification code:M6Special Provisions:274 335 601

Limited quantity: 5 L

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)

<u>14.1. UN number:</u> UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9Marine pollutant:p



Revision date: 13.04.2016

according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 10 of 11

Special Provisions: 274, 335
Limited quantity: 5 L
EmS: F-A, S-F

Other applicable information (marine transport)

E1

Air transport (ICAO)

<u>14.1. UN number:</u> UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

 14.3. Transport hazard class(es):
 9

 14.4. Packing group:
 III

 Hazard label:
 9

Special Provisions: A97 A158 Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

Other applicable information (air transport)

E1

Passenger-LQ: Y964

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

Danger releasing substance: epoxy resin

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: 4,4'-lsopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.



Revision date: 13.04.2016

according to Regulation (EC) No 1907/2006

CP-Synthofloor 8463 Part A

Print date: 28.04.2016 Page 11 of 11

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID:Règlement international conernat le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effectice concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)