

according to Regulation (EC) No 1907/2006

# Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 1 of 14

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Ceramic-Polymer KTW-1 Part A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Coatings and paints, fillers, putties, thinners

Uses advised against

No data available

## 1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	DE-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax:+49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	
1.4. Emergency telephone	+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)	

#### number:

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories: Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Regulation (EC) No. 1272/2008

### Hazard components for labelling

bis-[4-(2,3-epoxipropoxi)phenyl]propane 1,4-bis(2,3 epoxypropoxy)butane **Signal word:** Danger



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

**Pictograms:** 

Page 2 of 14



#### **Hazard statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

ecautionaly statement	113
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P391	Collect spillage.

#### 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	GHS Classification					
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane					
	216-823-5	216-823-5 603-073-00-2				
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens.	17 H411				
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane		8-10 %			
	219-371-7	01-2119494060-45				
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H332 H312 H302 H315 H318 H317 H412					

Full text of H and EUH statements: see section 16.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 3 of 14

### After inhalation

In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately. Do not wash with: Solvents/Thinner

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Do NOT induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO2). alcohol resistant foam. Water spray jet

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx)

## 5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8. Provide adequate ventilation. Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

## 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 4 of 14

recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

See protective measures under point 7 and 8. Disposal: see section 13

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8). Keep container tightly closed.

#### Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

#### Hints on joint storage

Keep away from: Food and feedingstuffs Oxidising agent

### Further information on storage conditions

Keep away from: Frost Heat Humidity

## 7.3. Specific end use(s)

No information available.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 5 of 14

## DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane			
Worker DNEL	_, long-term	inhalation	local	310 mg/m <sup>3</sup>
Consumer DI	NEL, long-term	inhalation	local	55 mg/m³
Worker DNEL	_, long-term	inhalation	systemic	4,93 mg/m³
Worker DNEL	., long-term	dermal	systemic	0,75 mg/kg bw/day
Consumer DI	NEL, long-term	inhalation	systemic	0,87 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,0893 mg/kg bw/day
Consumer DI	NEL, long-term	oral	systemic	0,5 mg/kg bw/day
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane			
Worker DNEL	_, long-term	inhalation	systemic	4,7 mg/m³
Worker DNEL	., long-term	dermal	systemic	6,66 mg/kg bw/day
Consumer DI	NEL, long-term	inhalation	systemic	1,16 mg/m³
Consumer DI	NEL, long-term	dermal	systemic	3,33 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	0,33 mg/kg bw/day
,				



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 6 of 14

#### **PNEC** values

CAS No	Substance	
Environmenta	l compartment	Value
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	
Freshwater		0,006 mg/l
Freshwater (i	ntermittent releases)	0,018 mg/l
Marine water		0,001 mg/l
Freshwater se	ediment	0,341 mg/kg
Marine sedim	ent	0,034 mg/kg
Secondary po	isoning	11 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	10 mg/l
Soil		0,065 mg/kg
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane	
Freshwater		0,024 mg/l
Freshwater (in	ntermittent releases)	0,24 mg/l
Marine water		0,002 mg/l
Freshwater se	ediment	0,084 mg/kg
Marine sediment		0,008 mg/kg
Secondary po	isoning	0,028 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	100 mg/l
Soil		0,003 mg/kg

#### 8.2. Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

#### Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

#### Eye/face protection

Suitable eye protection: Eye glasses with side protection goggles

## Hand protection

Tested protective gloves must be worn: EN ISO 374 NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber) Wearing time with permanent contact: Thickness of the glove material: >= 0,4 mm, Breakthrough time

(maximum wearing time): >480 min

Wearing time with occasional contact (splashes):: Thickness of the glove material: >= 0,1 mm, Breakthrough time (maximum wearing time) > 30 min



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 7 of 14

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Breakthrough times and swelling properties of the material must be taken into consideration.

#### Skin protection

Protective clothing

#### **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device (EN 14387) A-P3 Self-contained respirator (breathing apparatus) (DIN EN 133)

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid	
Odour:	characteristic	
pH-Value:		No data available
Changes in the physical state		
Melting point:		No data available
Initial boiling point and boiling range:		No data available
Sublimation point:		No data available
Softening point:		No data available
Pour point:		No data available
Flash point:		> 100 °C
Flammability		
Solid:		No data available
Gas:		No data available
Explosive properties No information available.		
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Ignition temperature:		No data available
Auto-ignition temperature		
Solid:		No data available
Gas:		No data available
Decomposition temperature:		No data available
Oxidizing properties No information available.		
Vapour pressure:		No data available



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer KTW-1 Part A

Page 8 of 14

	Density:	No data available
	Water solubility:	No data available
	Solubility in other solvents No information available.	
	Partition coefficient:	No data available
	Viscosity / dynamic:	No data available
	Vapour density:	No data available
	Evaporation rate:	No data available
<u>9.</u>	2. Other information	

No information available.

Revision date: 17.01.2020

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

### 10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Acid, Oxidising agent

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

### 10.5. Incompatible materials

Acid, Oxidising agent

#### 10.6. Hazardous decomposition products

Does not decompose when used for intended uses. No known hazardous decomposition products.

### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

### Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 9 of 14

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
1675-54-3	bis-[4-(2,3-epoxipropoxi)	phenyl]prop	bane				
	oral	LD50 mg/kg	19800	Rabbit	Publication (1958)	Rabbits were orally gavaged with test ma	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2007)	OECD Guideline 402	
	inhalation (4 h) vapour	LC50 mg/l	ca. 24,6	Rat	AMA Arch. Ind. Hyg. Occ. Med. 10: 61-68	Rats were exposed to 8000 ppm of the tes	
2425-79-8	1,4-bis(2,3 epoxypropox	y)butane					
	oral	LD50 mg/kg	1163	Rat	Study report (1988)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 2150	Rat	Study report (1972)	OECD Guideline 402	
	inhalation vapour	ATE	11 mg/l				
	inhalation aerosol	ATE	1,5 mg/l				

## Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

## Sensitising effects

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxi)phenyl]propane; 1,4-bis(2,3 epoxypropoxy)butane)

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

No information available.



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 10 of 14

CAS No	Chemical name	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
1675-54-3	54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane							
	Acute fish toxicity	LC50	3,6 mg/l	96 h	Oncorhynchus mykiss	Study report (1982)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella subcapitata	Study report (2007)	OECD Guideline 201	
	Acute crustacea toxicity	EC50	2,8 mg/l	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202	
	Crustacea toxicity	NOEC	0,3 mg/l	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211	
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane							
	Acute algae toxicity	ErC50 mg/l	> 160	72 h	Pseudokirchneriella subcapitata	Study report (2010)	OECD Guideline 201	

## 12.2. Persistence and degradability

No information available.

## 12.3. Bioaccumulative potential

No information available.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	>= 2,64
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane	-0,269

BCF

CAS No	Chemical name	BCF	Species	Source
	bis-[4- (2,3-epoxipropoxi)phenyl]propane	31		Study report (2010)

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## **Disposal recommendations**

Dispose of waste according to applicable legislation.



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 11 of 14

## Contaminated packaging

Dispose of waste according to applicable legislation.

## **SECTION 14: Transport information**

Land transport (ADR/RID)			
<u>14.1. UN number:</u>	UN 3082		
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)		
14.3. Transport hazard class(es):	9		
14.4. Packing group:	III		
Hazard label:	9		
Classification code:	M6		
Special Provisions:	274 335 375 601		
Limited quantity:	5 L		
Excepted quantity:	E1		
Transport category:	3		
Hazard No:	90		
Tunnel restriction code:	-		
Inland waterways transport (ADN)			
<u>14.1. UN number:</u>	UN 3082		
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)		
14.3. Transport hazard class(es):	9		
14.4. Packing group:	III		
Hazard label:	9		
Classification code:	M6		
Special Provisions:	274 335 375 601		
Limited quantity:	5 L		
Excepted quantity:	E1		
Marine transport (IMDG)			
<u>14.1. UN number:</u>	UN 3082		
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)		
14.3. Transport hazard class(es):	9		
14.4. Packing group:	III		
Hazard label:	9		
Special Provisions:	274, 335, 969		
Limited quantity:	5 L		
Excepted quantity:	E1		
EmS:	F-A, S-F		
Air transport (ICAO-TI/IATA-DGR)			



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer KTW-1 Part A

evision date: 17.01.2020	Page 12 o
<u>14.1. UN number:</u>	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Special Provisions:	A97 A158 A197
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y964
Excepted quantity:	E1
IATA-packing instructions - Passenger:	964
IATA-max. quantity - Passenger:	450 L
IATA-packing instructions - Cargo:	964
IATA-max. quantity - Cargo:	450 L
.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	yes
Danger releasing substance:	epoxy resin
.6. Special precautions for user No information available.	
4.7. Transport in bulk according to Annex No information available.	II of Marpol and the IBC Code
ECTION 15: Regulatory information	
5.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.
Water contaminating class (D):	2 - clearly water contaminating
5.2. Chemical safety assessment	
	ixture a chemical safety assessment has been carried out: ne
1,4-bis(2,3 epoxypropoxy)butane	

This data sheet contains changes from the previous version in section(s): 3.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 13 of 14

(European Agreement concerning the International Carriage of Dangerous Goods by Road ) RID:Règlement international conernat le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals UN: United Nations CAS: Chemical Abstracts Service DNEL: Derived No Effect Level DNEL: Derived No Effect Level PNEC: Predicted No Effect Level PNEC: Predicted No Effect Level PNEC: Predicted No Effect Level CSO: Lethal concentration, 50% LD50: Lethal loading, 50% EL50: Effect loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration foor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern

## Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer KTW-1 Part A

Revision date: 17.01.2020

Page 14 of 14

H412

Harmful to aquatic life with long lasting effects.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)