

according to Regulation (EC) No 1907/2006

# Ceramic-Polymer STP-EP2 (AWWA) Part A

Print date: 06.03.2017 Page 1 of 9

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Ceramic-Polymer STP-EP2 (AWWA) Part A

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Coatings and paints, fillers, putties, thinners

# 1.3. Details of the supplier of the safety data sheet

Company name: Ceramic Polymer GmbH

Street: Daimlerring 9

Place: DE-32289 Rödinghausen
Telephone: +49(0) 52 23 / 9 62 76-0 Telefax: +49(0) 52 23 / 9 62 76-17

e-mail: info@ceramic-polymer.de Internet: www.ceramic-polymer.de Responsible Department: info@ceramic-polymer.de

**1.4. Emergency telephone** +49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

number:

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Causes skin irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

# 2.2. Label elements

#### Regulation (EC) No. 1272/2008

# Hazard components for labelling

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

1,6-bis(2,3-epoxypropoxy)hexane

Signal word: Warning

Pictograms:





# **Hazard statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H411 Toxic to aquatic life with long lasting effects.

# **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P309+P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer STP-EP2 (AWWA) Part A

Print date: 06.03.2017 Page 2 of 9

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P362+P364 Take off contaminated clothing and wash it before reuse.

P273 Avoid release to the environment.

P270 Do not eat, drink or smoke when using this product.

P403+P235 Store in a well-ventilated place. Keep cool.

#### Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

## 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			25-<50 %
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane			1-<5 %
	240-260-4		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412			

Full text of H and EUH statements: see section 16.

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

# General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately. Do not wash with: Solvents/Thinner

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

# After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Immediate medical treatment required because corrosive injuries that are not treated are hard to cure. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

## 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer STP-EP2 (AWWA) Part A

Print date: 06.03.2017 Page 3 of 9

After contact with skin, wash immediately with plenty of Lutrol.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO2). alcohol resistant foam. Water spray jet

### Unsuitable extinguishing media

High power water jet

### 5.2. Special hazards arising from the substance or mixture

Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx)

#### 5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

Provide adequate ventilation.

Personal protection equipment: see section 8

Remove persons to safety.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

# 6.4. Reference to other sections

See protective measures under point 7 and 8.

Disposal: see section 13

## **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

### Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8). Keep container tightly closed.

### Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

## Advice on storage compatibility

Keep away from:

Food and feedingstuffs

Oxidising agent

# Further information on storage conditions

Keep away from:

Frost

Heat



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer STP-EP2 (AWWA) Part A

Print date: 06.03.2017 Page 4 of 9

Humidity

#### 7.3. Specific end use(s)

No information available.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

## **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol					
Worker DNEL,	long-term	inhalation	systemic	29,39 mg/m³		
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day		
Worker DNEL,	acute	dermal	local	0,0083 mg/cm <sup>2</sup>		
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane					
Consumer DNE	EL, acute	inhalation	systemic	2,9 mg/m³		
Consumer DNEL, long-term		inhalation	local	0,27 mg/m³		
Consumer DNEL, long-term		dermal	systemic	1,7 mg/kg bw/day		
Consumer DNE	Consumer DNEL, acute		systemic	1,7 mg/kg bw/day		
Consumer DNEL, long-term		dermal	local	0,0136 mg/cm <sup>2</sup>		
Consumer DNEL, acute		dermal	local	0,0136 mg/cm <sup>2</sup>		
Consumer DNEL, long-term		oral	systemic	0,83 mg/kg bw/day		
Consumer DNEL, acute		oral	systemic	0,83 mg/kg bw/day		
,						

### **PNEC values**

CAS No	Substance		
Environmental compartment Value			
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol		
Freshwater 0,003 mg/l		0,003 mg/l	
Freshwater sediment 0,294 mg/kg		0,294 mg/kg	
Marine sediment		0,029 mg/kg	
Soil		0,237 mg/kg	

## 8.2. Exposure controls

### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

## Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

### Eye/face protection

Suitable eye protection: Eye glasses with side protection goggles



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer STP-EP2 (AWWA) Part A

Print date: 06.03.2017 Page 5 of 9

#### Hand protection

Suitable gloves type:

NBR (Nitrile rubber) DIN EN 374.

Butyl caoutchouc (butyl rubber) DIN EN 374

Wear cotton undermitten if possible.

#### Skin protection

Protective clothing

## Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn

Combination filtering device (EN 14387) A-P3

Self-contained respirator (breathing apparatus) (DIN EN 133)

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour:

Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Sublimation point:

Softening point:

Pour point:

Flash point:

not determined

not determined

not determined

not determined

not determined

not determined

>95 °C

**Flammability** 

Solid: not determined
Gas: not determined

**Explosive properties** 

No information available.

Lower explosion limits:

Upper explosion limits:

Ignition temperature:

not determined

not determined

**Auto-ignition temperature** 

Solid: not determined Gas: not determined
Decomposition temperature: not determined

**Oxidizing properties** 

No information available.

Vapour pressure: not determined

Density (at 23 °C): ~1,4 g/cm³

Water solubility: not determined

Solubility in other solvents

No information available.



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer STP-EP2 (AWWA) Part A

Print date: 06.03.2017 Page 6 of 9

Partition coefficient: not determined Viscosity / dynamic: not determined (at 23 °C)

Vapour density: not determined Evaporation rate: not determined

### 9.2. Other information

No information available.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

Reacts with: Acid, Oxidising agent

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

#### 10.5. Incompatible materials

Acid, Oxidising agent

## 10.6. Hazardous decomposition products

Thermal decomposition

Hazardous decomposition products: Gases

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

### **Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol					
	oral	LD50	>5000 mg/kg	rat (male/female)	ECHA	
	dermal	LD50	>2000 mg/kg	rat (male/female)	ECHA	

#### Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

May cause an allergic skin reaction.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

## Ceramic-Polymer STP-EP2 (AWWA) Part A

Print date: 06.03.2017 Page 7 of 9

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

No information available.

#### 12.2. Persistence and degradability

No information available.

#### 12.3. Bioaccumulative potential

No information available.

# 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Advice on disposal

Dispose of waste according to applicable legislation.

## Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

#### **SECTION 14: Transport information**

## Land transport (ADR/RID)

<u>14.1. UN number:</u> UN 3082

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9Classification code:M6

Special Provisions: 274 335 601

Limited quantity: 5 L
Transport category: 3
Hazard No: 90
Tunnel restriction code: E

## Other applicable information (land transport)

E1

# Inland waterways transport (ADN)

<u>14.1. UN number:</u> UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

 14.3. Transport hazard class(es):
 9

 14.4. Packing group:
 III

 Hazard label:
 9

 Classification code:
 M6

Special Provisions: 274 335 601

Limited quantity: 5 L



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer STP-EP2 (AWWA) Part A

Print date: 06.03.2017 Page 8 of 9

### Other applicable information (inland waterways transport)

F1

#### Marine transport (IMDG)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

 14.3. Transport hazard class(es):
 9

 14.4. Packing group:
 III

 Hazard label:
 9

 Marine pollutant:
 p

Special Provisions: 274, 335 Limited quantity: 5 L EmS: F-A, S-F

### Other applicable information (marine transport)

F1

## Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u> UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9

Special Provisions: A97 A158 Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

## Other applicable information (air transport)

E1

Passenger-LQ: Y964

## 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

Danger releasing substance: epoxy resin

## 14.6. Special precautions for user

No information available.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water contaminating class (D): 2 - water contaminating



according to Regulation (EC) No 1907/2006

# Ceramic-Polymer STP-EP2 (AWWA) Part A

Print date: 06.03.2017 Page 9 of 9

#### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol 1,6-bis(2,3-epoxypropoxy)hexane

#### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID:Règlement international conernat le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effectice concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

## Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)